

Shielded flat audio cables



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
TSK 1054	4	4 x 0,12 (26 AWG)	16x0,10	1,1	2,5 x 10,1	100	B	4,0

Applications:
Extra flex divisible shielded flat cable for sound reproduction and electronics.
Suitable for the realization of audio assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: PVC
 Core colours: Yellow, Blue, White, Red
 Shields: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Blue-night

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
140	56	340
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C180	3	3 x 0,14 (26 AWG)	18x0,10	1,1	2,8 x 8,4	100	B	3,5
C119	4	4 x 0,14 (26 AWG)	18x0,10	1,1	2,8 x 12,0	100	B	5,0

Applications:
Divisible shielded flat cable for sound reproduction and electronics.
Suitable for the realization of audio assembly.

Characteristics:
 Conductors: O.F.C. red copper
 Cond. Insulation: PVC
 Core colours: Black, White, Red, Yellow
 Shields: Spiral covering 100%
 O.F.C. red copper
 Sheath: PVC
 Sheath colour: Black

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
130	65	350
130	65	350
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70